



FlexLine FLE-TPRO (electrodes) technical data

A higher humidification performance is possible by connecting units together.

Type	FLE15-TPRO	FLE20-TPRO	FLE25-TPRO	FLE30-TPRO	FLE40-TPRO	FLE50-TPRO	FLE65-TPRO
Steam output [kg/h]	15	20	25	30	40	50	65
Electrical connection ⁽¹⁾	400V / 3Ph / N / 50-60Hz						
Rated power [kW]	11.2	15.0	18.8	22.5	30.0	37.5	48.8
Nominal current [A]	16.2	21.7	27.1	32.5	43.3	54.1	70.4
Fuse [A] ⁽²⁾	3 x 20	3 x 32		3 x 40	3 x 50	3 x 63	3 x 80
Number of steam cylinder	1						
Control	FlexLine mainboard Process with capacitive 3.5" touch colour display						
Internal control voltage ⁽³⁾	220-240V / N / 2.5A						
Steam hose connection [mm]	1 x 25	1 x 40		2 x 40 ⁽⁴⁾		2 x 40	
Max. filling capacity [l]	13		21		36		
Empty weight [kg]	22		23	26		33	34
Operating weight [kg]	36		37	47		69	70
Dimensions WxHxD [mm] ⁽⁵⁾	540 x 695 x 320			580 x 750 x 355		640 x 785 x 420	
Water connection	Tap water of varying qualities, 1 to 10 bar, for 3/4" external thread						
Drain water connection	Connection Ø 1 1/4"						

We reserve the right to make technical changes.

- (1) Other voltages upon request.
- (2) 13/28% above nominal power consumption after full blowdown. Observe actuation characteristics of automatic circuit-breakers. If necessary, select the next highest circuit-breaker level.
- (3) Separate control voltage upon request.
- (4) Incl. Y-piece DN40.
- (5) Outer dimensions of width and depth. Height incl. drain connection.



HygroMATIK[®]
member of CAREL group 

HygroMatik GmbH

Lise-Meitner-Str. 3
24558 Henstedt-Ulzburg
Germany

T +49 4193 895-0
hy@hygromatik.de
www.hygromatik.com